

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims of the application:

LISTING OF CLAIMS:

Claims 1 to 23. (Cancelled).

24. (New) A terminal end-piece for a fuel assembly of a pressurized water nuclear reactor, the assembly comprising fuel rods and a skeleton for supporting the fuel rods, the fuel rods extending in a longitudinal direction and being arranged at nodes of a substantially regular network, the support skeleton comprising two terminal end-pieces and guide tubes that connect the terminal end-pieces, the fuel rods being arranged longitudinally between the terminal end-pieces, comprising:

noses for orientating flow of a coolant fluid of the reactor along adjacent longitudinal ends of the fuel rods, the noses being arranged at least one of in the nodes of the substantially regular network in order to be positioned in a longitudinal continuation of at least some of the fuel rods and at least some of the guide tubes of the support skeleton.

25. (New) The end-piece according to claim 24, wherein the noses converge in a direction that is orientated towards an outer side of the fuel assembly.

26. (New) The end-piece according to claim 24, wherein at least some of the noses belong to members for fixing the terminal end-piece to one of guide tubes of the support skeleton and fuel rods.

27. (New) The end-piece according to claim 26, wherein the fixing members are screws.

28. (New) The end-piece according to claim 24 further comprising:
an arrangement for laterally maintaining the adjacent longitudinal ends of the fuel rods, wherein the arrangement is arranged in the nodes of the substantially regular network.

29. (New) The end-piece according to claim 28, wherein the maintenance housing further comprises housings for receiving the adjacent longitudinal ends of the fuel rods.
30. (New) The end-piece according to claim 28, wherein the maintenance arrangement has an arrangement for longitudinally securing the adjacent longitudinal ends of the fuel rods relative to the terminal end-piece.
31. (New) The end-piece according to claim 30, wherein the end-piece comprises two components for clamping between them the adjacent longitudinal ends of the fuel rods.
32. (New) The end-piece according to claim 24, wherein the end piece comprises an anti-debris filter.
33. (New) The end-piece according to claim 31, wherein one of the components comprises an anti-debris filter.
34. (New) The end-piece according to claim 24, wherein the end piece further comprises a bottom end piece.
35. (New) The end-piece according to claim 34, wherein the end piece comprises feet for support on a lower plate of the nuclear reactor core.
36. (New) A fuel assembly for a pressurized water nuclear reactor, the assembly comprising:
fuel rods; and
a skeleton for supporting the fuel rods, the fuel rods extending in a longitudinal direction and being arranged at nodes of a substantially regular network, the support skeleton comprising two terminal end-pieces and guide tubes that connect the terminal end-pieces, the fuel rods being arranged longitudinally between the terminal end-pieces, wherein at least one end-piece is an end-piece having noses for orientating flow of a coolant fluid of the reactor along adjacent longitudinal ends of the fuel rods, the noses being arranged at least one of in the nodes of the substantially regular network in

order to be positioned in a longitudinal continuation of at least some of the fuel rods and at least some of the guide tubes of the support skeleton.

37. (New) The assembly according to claim 36, wherein the end-piece comprises an arrangement for laterally maintaining adjacent longitudinal ends of the fuel rods, wherein the arrangement is configured in nodes of the substantially regular network.

38. (New) The assembly according to claim 37, wherein the arrangement comprises housings that receive the adjacent longitudinal ends of the fuel rods.

39. (New) The assembly according to claim 37, wherein the maintenance arrangement is an arrangement for longitudinally securing the adjacent longitudinal ends of the fuel rods relative to the terminal end-piece.

40. (New) The assembly according to claim 39, wherein the end-piece comprises two components that clamp between them the adjacent longitudinal ends of the fuel rods.

41 (New) The assembly according to claim 40, wherein the longitudinal securing arrangement comprises projections that are provided on the end-piece and rings that are provided at the adjacent longitudinal ends of the fuel rods and that are fitted to the projections.

42. (New) The assembly according to claim 41, wherein that the rings comprise relief portions for abutment against one of the components.

43. (New) The assembly according to claim 38, wherein the adjacent longitudinal ends of the fuel rods comprise widened feet that are clamped between the two components.

44. (New) The assembly according to claim 37, wherein the adjacent longitudinal ends of the fuel rods are expansion-rolled on the end-piece.

45. (New) The assembly according to claim 39, wherein the longitudinal securing arrangement comprises screws that abut the end-piece and that are engaged in the adjacent longitudinal ends of the fuel rods.

46. (New) The assembly according claim 39, wherein the longitudinal securing arrangement secures by snap-fitting.